

WOODS **GROUNDMOVER-X™**

RUGGED **CURVED** BOOM LOADERS
FOR COMPACT TRACTORS

PERFORMANCE GUIDE

Alone, or with available attachments, perfect for homeowners, landscapers or the professional contractor.



Pictured, Woods Model LC114.
Also available in the LC Series,
the Model LC108.

WOODS LC SERIES GROUNDMOVER-X™ LOADERS *For tractors 28-50 hp*

The Woods Groundmover-X™ LC Series loaders continue the Woods tradition of being “Tested. Proven. Unbeatable.” With over 50 years in the loader business, our new LC108 and LC114 loaders provide users with the ability to complete virtually every rugged job faced, while delivering years of worry-free service!

Features

LC Series loader mounts utilize the structural integrity inherent in 28 to 50 horsepower compact tractors and feature a center-point attachment—reducing obstructions and providing a much cleaner, more integrated look.

A wrenchless, 2-pin mid-attach mount design allows for quick attaching and detaching of the loader boom from the tractor. Simply set the bucket on the ground, roll to release pressure on attachment pins, and set loader stand. Pull the attachment pins by hand, detach hydraulics, then drive out.



mid-attach boom



jack stand storage



bucket level rod



4-bar linkage system



optional quick-attach

WOODS
The Attachment Experts.™

WOODS **GROUNDMOVER-X™** LOADER

Specifications

| Model | LC108 | LC114 |
|--|---------------|---------------|
| Tested hydraulic PSI | 2,500 psi | 2,500 psi |
| Lift capacity at bucket pin | 2,175 lbs | 2,400 lbs |
| Breakout at bucket pin | 3,850 lbs | 4,600 lbs |
| Lift capacity at 19.7" ahead of bucket pins | 1,800 lbs | 1,950 lbs |
| Breakout at 19.7" ahead of bucket pins | 3,000 lbs | 3,400 lbs |
| Maximum lift height | 108" | 114" |
| Clearance under bucket | 83" | 90" |
| Reach at maximum height | 40" | 32" |
| Bucket roll back angle | 35° | 35° |
| Bucket dump angle | 58° | 50° |
| Maximum digging depth | 5" | 5" |
| Lift cylinder diameter | 2.36" | 2.48" |
| Bucket cylinder diameter | 2.36" | 2.36" |
| Recommended tractor horsepower | 28-50 | 30-50 |
| Bucket widths | 60", 66", 72" | 60", 66", 72" |
| Bucket rated capacity c.c. ft. (60" / 66" / 72") | 11.6/12.8 /14 | 11.6/12.8 /14 |
| Pivot pins diameter | 1.25" | 1.25" |

Tractor Color Coordinated*

Available in colors to match your particular tractor.



* Woods loaders come available painted to match Kubota® orange, New Holland® blue, John Deere® green, Case IH® red, Cub Cadet® yellow, Massey Ferguson® red or universal black.

Designed with the operator in mind, Woods LC Series loaders provide optimal tire clearance and excellent visibility from the operator's control center, while also maximizing lift height, breakout and lift capacities.

Additional Features

Commercial grade bucket – increases bucket efficiency with round-back bucket design, engineered to allow easy and even material flow, into and out of bucket.

Mid-attaching loader boom – provides less obstruction along the side and front of tractor, reducing tire interference for greater turning flexibility and shorter turn radius.

4-bar bucket linkage – allows for 35-degree bucket roll-back angle to carry full loads without loss, and up to 58-degree bucket dump angle to ensure complete emptying.

High performance, multi-function loader control valve – creates faster regenerative valve action. While bucket returns from dump position to loading position, oil flow from lift cylinders directs to bucket cylinders, leveling the bucket.

Optional Attachments

Quick Attach Carrier System – allows for quick attaching and detaching of various attachments, including:

- Multi-purpose Buckets
- Bolt-on Cutting Edges
- Manure Fork
- Scrap Grapple Bucket
- Utility Forks and Grapple
- Round Bale Spear
- Square Bale Spear
- Pallet Forks
- Angle Brooms

Insist on genuine WoodsCare™ parts for genuine Woods performance.



The Attachment Experts.™

Woods Equipment Company 2606 South Illinois Route 2, PO Box 1000, Oregon, Illinois 61061 tel 800-319-6637 www.WoodsEquipment.com

WARNING! Some images may show safety equipment removed to provide a better view. Equipment should never be operated without required safety equipment.

Always operate machine in accordance with supplied operator's manuals. Some machines in this brochure may be shown with optional equipment. Specifications are subject to change without notice.

Case IH and International are registered trademarks of CNH America LLC. Cub Cadet is a registered trademark of MTD Products Inc. John Deere is a registered trademark of Deere & Company Corporation.

Kubota is a registered trademark of Kubota Corporation. Massey Ferguson is a registered trademark of AGCO Corporation. New Holland is a registered trademark and SuperSteer a trademark of New Holland.

Woods, the Woods logo, "Tested. Proven. Unbeatable.", and WoodsCare are trademarks or registered trademarks of Woods Equipment Company. ©2006 WEC Company d/b/a Woods Equipment Company. All rights reserved.

B-09064B