

# WOODS TBW150C TURF BATWING

12.5-FOOT FOLDING WING, FINISH MOWER



TBW150C shown with optional rear chain shielding.

## PERFORMANCE GUIDE

For wide area finish mowing with compact and utility size tractors.

Manufactured



In The U.S.A.

*The same experience, design, and technology that has made our name in agricultural cutters, goes into our Woods' folding wing, finish-mowers.*

Woods' new TBW150C Turf Batwing® wide area finish mower redefines the leisure time homeowners with large properties come to cherish.

With Woods' proven cutting deck in a three gang configuration and mounted to a heavy-duty trailer, this 12.5-foot mower provides a beautifully finished cut making short work of estate mowing. When compared to conventional mowing, Woods TBW150C has assisted some users in reducing two-days of mowing into as little as 4½ hours.

Each deck mows a 4 ½ foot path with a 6 inch overlap—assuring no path is left uncut when making turns. Cast iron, industrial quality, reinforced blade spindles with greaseable ball bearings (3 on each deck) offer strength and long life, while the cast iron spindle gearboxes offer a 3-year residential warranty. Woods' deep 4.6-inch deck allows even tall grass to be cut and discharged without loss of power and performance. Spring loaded idler pulleys maintain correct belt tension, offering significantly longer belt life and ensure heat-treated, alloy steel blades turn at proper blade tip speeds.



Welded to American Welding Society® standards.

## FEATURES

- Box construction on decks offer superior strength
- Heavy tubular caster arms mounted on 4.5-inch deck rail supports for long product life
- 4.6-inch deck depth with baffling around blades ensures exceptional material distribution and higher quality of cut
- Each deck includes three standard anti-scalp rollers to prevent scalping; optional rear chain shielding to reduce risk of thrown objects
- Fixed caster wheels on wing decks assures hillside stability
- Hydraulic wing and rear deck lifts with automatic locks; rope pull release
- Hydraulic unlock option available
- Optional mulch kits

# WOODS

The Attachment Experts.™

# WOODS REAR DISCHARGE TURF BATWING

## Specifications

### MEASUREMENTS

Model	TBW150C
Cutting width	12.5 feet
Cutting height range	1 – 4.5 inches
Deck cutting width	4.5 feet
Wing float	20° up / 15° down
Deck skirt depth	4.6 inches
Deck overlap	6 inches
Overall width	151 inches
Transport width	93 inches
Maximum overall length	135 inches
Transport length	126 inches
Transport height	71 inches
Minimum horsepower req.	25 hp
Splitter gearbox rating	100 hp
Deck gearbox rating	35 hp
Blade tip speed	18,000 fpm
Blade overlap	1-1/2 inches

### MATERIAL & CONSTRUCTION

Model	TBW150C
Input driveline	gearbox over v-belt
Input driveline	category 3 CV (constant velocity)
Wing drivelines	category 3
Transport tires	(2) 20 x 8
Caster wheel bearings	powder metal bushing
Caster wheels	(10) 4 x 10 solid
Deck thickness, material	10-gauge, steel plate
Wing deck lift cylinders	3" x 10", single acting
Center deck lift cylinder	3" x 8" single acting
Trailer frame construction	1/4" wall tube
Hitch type	clevis self-leveling, multi-position
Blade spindle bearings	greaseable ball bearing
Blade dimensions	(9) 1/4" x 2-1/2"
Blade composition	heat-treated alloy steel
Blade spindles	(9) cast-iron
Cutting height adjustment	spacer on caster
Belts	B-section, Kevlar
Belt adjustment	spring loaded idler
Anti-scalp rollers (frnt & back)	standard (3 per deck)
Hydraulic unlock	optional
Chain shielding (rear)	optional
Mulch kit	optional
Mower warranty	1-yr Residential/3-mos Commercial
Gearbox warranty	3-yr Residential/3-mos Commercial

### COMPATIBILITIES

Model	TBW150C
Tractor horsepower	25 – 60
Tractor PTO speed	540 rpm

### WEIGHTS

Model	TBW150C
Approximate weight	1,750 lbs.
Transport tongue weight	510 lbs.
Operating tongue weight	320 lbs.
Ground pressure	5.0 psi

### ADDITIONAL FEATURES

- Narrow transport width allows storage in standard size garage
- Superior B-section Kevlar® belts – long belt life and improved performance
- Fully baffled decks offer top quality cut and even discharge of grass
- Decks float independently to follow ground contours for best cut with reduced chance for scalping



Available in standard Woods burnt orange or colors to match major tractor brands (Orange, Vibrant Blue, Green and two Reds).



# WOODS

The Attachment Experts.™

**Woods Equipment Company**

2606 South Illinois Route 2, PO Box 1000, Oregon, Illinois 61061  
tel 800-319-6637 [www.WoodsEquipment.com](http://www.WoodsEquipment.com)

WARNING! Some images may show safety equipment removed to provide a better view. Equipment should never be operated without required safety equipment. Always operate machines in accordance with supplied operator's manuals. Some machines in this brochure may be shown with optional equipment. Specifications subject to change without notice. Woods, the Woods logo, "The Attachment Experts", and WoodsCare are trademarks of Woods Equipment Company. ©2008 Woods Equipment Company. All rights reserved. B-10081