

WOODS SNOW BLOWER

TRACTOR MOUNTED SNOW BLOWERS

STANDARD-DUTY 52-74" SS52, SS60, & SS74

Category 1, 20-50 hp tractors

- Single 15-inch heavy-duty feeder auger
- 1/4-inch flighting on feeder auger
- 3-blade, 23-inch diameter fan
- Hand crank chute rotator
- Optional hydraulic chute rotator
- Replaceable cutting edge

HEAVY-DUTY 84-108" SS84, SS96, & SS108

Category 2 & 3, 60-200 hp tractors

- Dual 15-inch heavy-duty feeder augers (single auger on SS84 model)
- 3/8-inch flighting on feeder augers
- Hydraulic chute rotator included
- 3-blade, 24-inch diameter fan
- Replaceable cutting edge



WOODS SNOW BLOWER

STANDARD-DUTY SS52, SS60, & SS74

Available in 52-74-inch wide models with 30-inch cutting heights.

Two stage design allows more throwing force with less horsepower than single stage models. In stage one, the auger bites into the snow and pulls it toward the fan. In stage two, the fan blades pick up the snow and blow it out the chute.

Design improvements to the chute, fan blade, and working height result in snow being picked up better, moved quicker, and thrown farther.

HEAVY-DUTY SS84, SS96, & SS108

Available in 84-108-inch wide models with 28-38-inch cutting heights.

Turn your tractor into a heavy-duty snow removal machine. Even large snow accumulation is no match for these snow blowers. Attach directly to your tractor's 3-point hitch for easy mounting and removal.

Two stage design provides reliable performance in heavy, wet, or even frozen snow. The standard hydraulic chute rotators allow you to direct snow placement precisely where you want.

WOODSSNOW BLOWER



Specifications

Model	SS52	SS60	SS74	SS84	SS96	SS108
Working width	52"	60"	74"	84"	96"	108"
Transport width	55.1"	63.1"	77.1"	87.7"	99.7"	111.7"
Working height	30"	30"	30"	28"	38"	38"
Approximate weight	438 lbs.	447 lbs.	507 lbs.	1,210 lbs.	1,420 lbs.	1,741 lbs.
Tractor horsepower	20-40	25-45	30-50	60-80	80-125	125-200
Tractor PTO speed	540 RPM	540 RPM	540 RPM	540 RPM	540/1000 RPM	540/1000 RPM
Hitch	category 1	category 1	category 1	category 2 & 3	category 2 & 3	category 2 & 3
Driveline	12R	12R	12R	44R	44R	44R
Driveline protection	5/16" shear pin	5/16" shear pin	5/16" shear pin	3/8" shear pin	3/8" shear pin	3/8" shear pin
Drive type—fan	gearbox	gearbox	gearbox	gearbox	gearbox	gearbox
Drive type—augers	gearbox & chain	gearbox & chain	gearbox & chain	gearbox & chain	gearbox & chain	gearbox & chain
Number of feeder augers	1	1	1	1	2	2
Auger flighting	1/4"	1/4"	1/4"	5/16"	5/16"	5/16"
Chute rotation	210°	210°	210°	200°, hydraulic	200°, hydraulic	200°, hydraulic
Hydraulic chute rotator	optional	optional	optional	standard	standard	standard
Fan diameter	23"	23"	23"	24"	34"	34"
Fan blades	1/4" plate	1/4" plate	1/4" plate	1/4" plate	1/4" plate	1/4" plate
Fan housing thickness	10 & 14 gauge	10 & 14 gauge	10 & 14 gauge	7 & 10 gauge	7 & 10 gauge	7 & 10 gauge
Main housing thickness	12 gauge	12 gauge	12 gauge	7 gauge	7 gauge	7 gauge
Side sheet thickness	10 gauge	10 gauge	10 gauge	1/4"	1/4"	1/4"
Replaceable skids	yes	yes	yes	yes	yes	yes
Adjustable skids	yes	yes	yes	yes	yes	yes
Replaceable cutting edge	yes	yes	yes	yes	yes	yes
Telescoping 3-point hitch	—	—	—	yes	yes	yes
	s t a n d a r d - d u t y			h e a v y - d u t y		



Insist on genuine WoodsCare™ parts for genuine Woods performance.

We manufacture a world of tools to make you more productive. **WoodsAgricultural™** offers tractor-powered productivity tools for cutting, shredding, and specialty agricultural applications. **WoodsLandscape™** provides tractor and self-powered tools for mowing, landscaping, and general grounds care. **WoodsConstruction™** supplies buckets, coupler systems, and other attachments for construction applications. **WoodsCare™** provides parts and services for the total ongoing care of your Woods equipment. **WoodsTisco™** supplies a comprehensive line of aftermarket replacement parts and accessories.

Woods Equipment Company

2606 South Illinois Route 2
Post Office Box 1000
Oregon, Illinois 61061

815-732-2141 tel
815-732-7580 fax
www.woodsonline.com



WARNING! Some illustrations may show safety shields removed to provide a better view. Equipment should never be operated with any safety shielding removed. Some machines in this catalog are shown with optional equipment. Always operate machines in accordance with supplied operating manuals. Specifications are subject to change without notice. ©2004 Woods Equipment Company. All rights reserved. F-016-PR (Rev. 05/04)