

# WOODS® ROTARY CUTTERS

20-foot batwing



**Make sure you check  
out Woods' 15-foot  
batwing series!**



# Batwing

20-foot folding-wing rotary cutter

## BW240 BW240HD

Rated for tractors  
70–200 hp



BW240 shown with chain shielding.

o v e r v i e w & f e a t u r e s

The Woods BW240 and BW240HD 20-foot rotary cutters are versatile, rugged, and built to handle a host of applications. Solid performers, these triple-spindle cutters meet the individual challenges they're designed to handle—whether it is mowing simple grass or cutting brush up to 3" in diameter. No longer do users have to buy more cutter than they need. The BW240 is in a class of its own. The BW240HD matches the best of the best. Both provide an economical choice when matching the right cutter with the right application.

Both Batwings provide excellent flotation on soggy grounds while improving such flotation with the use of dual wheels on the center section (standard) and wing sections (optional). Engineered to be pulled by utility size tractors 70 horsepower or more, the BW240 can also be pulled by tractors up to 160 PTO, while the BW240HD can be pulled by tractors up to 200 PTO.

Along with a deck rust-through warranty and gearbox warranty that's second to none, Woods proves once again why users view us as the attachment experts.

- 13.25" side frame depth; deepest in the industry
- Unique wing shape; for lower tongue weight and improved trimming
- Bolt-on skid shoes with "approachable" leading edge
- Standard baffling in each deck for even distribution of material
- Full length, 1" wing hinge pin

- 10-Year Deck Rust-Through Warranty
- 6-Year (BW240) and 7-Year (BW240HD) Gearbox Warranty (Limited)
- Full length "bolt-on" skid shoes
- Heavy-duty Category 6 CV input drive, or Category 5 heavy equal angle input drive
- Standard spring wheel yoke arms
- Walking tandem axle available
- Meets AWS® Certification welding standards

**1 Exclusive "quick-change" blade system** allows for easy changing of blades.

**2 Smooth, sloped top deck** sheds water and debris to prevent rust and corrosion.

**3 "Bolt-on" skid shoes with "approachable" leading edge** are replaceable and reduce sod damage when turning.

**4 Greaseable pivot points** are located on turnbuckle and axle arms and increase durability and reduce wear.

### PERFORMANCE GUIDE

#### BW240

Ideal for grassy fields, pastures, waterways and brush up to 2" in diameter.

#### BW240HD

Ideal for utility mowing, heavy grass and weeds, waterways, ditches and brush up to 3" in diameter.



# Batwing

20-foot folding-wing

## BW2400X

Rated for tractors  
75–250 hp



BW2400X shown with chain shielding.

o v e r v i e w & f e a t u r e s

The Woods BW2400X extreme-duty, 20-foot rotary cutter—versatile, rugged, and built to handle a host of applications. A solid performer, this triple-spindle, double-deck cutter meets the challenges of grassy fields, pastures, waterways, cornstalk shredding and brush up to 4" in diameter.

With a 12.5" side frame depth increasing its capacity for cut material, the BW2400X earns the distinction of possessing the deepest deck in the industry. With its unique double-deck design, this cutter maintains a cut quality far beyond the competition while protecting the top deck from being dented and resulting in diminished performance—placing the BW2400X in an exclusive class by itself.

Sporting several of the same features found in the Woods Batwing family of cutters, a 10-year deck rust-through warranty and 8-year gearbox warranty prove once again why users look to Woods as the attachment experts.

### PERFORMANCE GUIDE

Ideal for grassy fields, pastures, waterways, cornstalk shredding and brush up to 4" in diameter.



rotary cutter



# Batwing

## 13.5-foot folding-wing rotary cutter

### BW1620

Rated for tractors  
75–200 hp



BW1620 shown with chain shielding.

features

overview & features

- 12.5" side frame depth
- Unique wing shape to trim closer to objects
- Standard baffling in each deck for even distribution of material
- Full length, 1" wing hinge pin
- 10-Year Deck Rust-Through Warranty; 2 layers of 10-gauge deck plating
- 8-Year Gearbox Warranty (Limited)
- Operator's manual container
- Springs on each wheel arm
- Walking tandem axle available
- Blade deck rings available
- Stalk shredder kit available
- Pintel ring hitch available
- Meets AWS® Certification welding standards
- Heavy-duty Category 6 CV input drive, or Category 5 heavy equal angle input drive
- Innovative wing design allows trimming and mowing close to objects
- Optional dual tires available for wings

- 1 "Bolt-on" skid shoes with "approachable" leading edge** are replaceable and reduce sod damage when turning.
- 2 Woods' Exclusive "quick-change" blade system** allows for easy changing of blades.
- 3 Smooth, sloped top, fully welded double deck** sheds water and debris to prevent rust and corrosion.
- 4 Greaseable pivot points** are located on turnbuckle and axle arms to increase durability and reduce wear.



Touted as the "World's Toughest Single-Wing Batwing", this 13-1/2' flexible rotary cutter can handle brush up to 4" in diameter. The BW1620 comes loaded with specifications, features, and options making this unit the leader in its class.

- Heavy-duty Category 6 CV input drive, or Category 5 heavy equal angle input drive
- Smooth, sloped deck sheds water & debris
- 250/210 hp gearboxes with 8-year limited warranty ensure years of worry-free performance
- Standard baffles ensure even distribution of cut material
- 12.5" deep side frame provides maximum material capacity
- Innovative wing design allows trimming and mowing close to objects
- 3/8", full-length, bolt-on replaceable side skids with formed anti-scalp angle
- Choice of right or left wing
- Available with laminated or used aircraft tires
- Optional dual tires available for wings


- **Optional Equipment**—Deck rings; Single row or double row chain shielding; Pintel ring hitch for extra durability

- 1 Greaseable pivot points** are located on turnbuckle and axle arms to increase durability and reduce wear.
- 2 Self-leveling, swivel clevis hitch is standard**, reducing stresses to the BW1620 when operating on uneven terrain.
- 3 Heavy-duty skid shoes with an "approachable" leading edge** reduce sod damage when turning.
- 4 The deck design and baffling in each deck section helps recut material**, ensuring a finer shred and more even distribution.



Wing flexes 90° up and 22° down.

**PERFORMANCE GUIDE**  
Ideal for maintaining road right-of-ways and cutting grassy fields, pastures, waterways and light brush up to 4" in diameter.



13" deep side frame allows for greater material capacity.

# WOODS® Batwing 20-foot rotary cutters

## Specifications

		BW240/BW240HD	BW2400X	BW1620
Capacity	Cutting swath, in.	240"	240"	162"
	Cutting height, in.	2–15"	2–15"	2–15"
	Cutting capacity (dia.) in.	2" / 3" diameter	4" diameter	4" diameter
	Side frame depth, in.	13.25"	12.5"	12.5"
Tractor compatibility	Tractor PTO hp range	70–160 hp/70–200 hp	75–250 hp	75–250 hp
	Tractor PTO (RPM)	540/1,000 rpm	540/1,000 rpm	540/1,000 rpm
	Static vert drawbar load lb	2,400 w/chains	2,700 w/chains	2,870 w/chains
	Hitch	Pull-type, self level clevis	Pull-type, self level clevis	Standard self-leveling swivel clevis; optional pintel ring
Dimensions	Transport width, in.	123"	123"	100"
	Overall width/length, in.	250/198"	250/198"	171"/198"
	Deck type	Smooth, sloped	Smooth, sloped double-deck	Smooth, sloped double-deck
	Deck thickness	0.135	0.135/0.135 upper/lower	0.135/0.135 upper/lower
	Side frame thickness, in.	0.25"	0.25"	0.25"
	Hinges	Continuous	Continuous	Continuous
	Approx. weight, lb	6,510/6,600 lbs w/chains	7,740 lbs w/chains	8,500 lbs w/chains
Drivelines	Main	Cat. 6 CV or Cat 5 hvy 3 joint	Cat. 6 CV or Cat 5 hvy 3 joint	Cat. 6 CV or Cat. 5 wing drive
	Connecting	Cat. 4 telescoping profile	Cat. 5 telescoping profile	Cat. 5 telescoping profile
Gearcases	Number	4	4	3
	Vertical shaft size, in.	2" / 2.38"	2.38"	2.38"
	Splitter hp (spindle hp)	235 (120)/235 (190) hp	250/205 hp	250/205 hp
Blades	Thickness, in.	1/2"	1/2"	1/2"
	Width, in.	4"	4"	4"
	Type	Hi-lift, flat	Hi-lift, flat or shredder kit	Hi-lift, flat
	Overlap, in.	6"	6"	6"
	540 RPM	15,450 FPM	15,437/15,674 FPM	15,437/15,674 FPM
	1,000 RPM	16,300 FPM	16,915/16,659 FPM	16,915/16,659 FPM
	Material flow system	Standard baffles	Standard baffles	Standard baffles
Stump jumper/type	Standard/round welded	Standard/round welded	Standard/round welded	
Hydraulics—wing flex, degrees		90° up, 22° down	90° up, 22° down	Left or right wing; 90° up, 22° down
Wheels	Wheels type	21" Laminated, 24" Pneumatic or foam filled used Aircraft, 29" Pneumatic or foam filled used Aircraft, 15" Wheels less tires	21" Laminated, 24" Pneumatic or foam filled used Aircraft, 29" Pneumatic or foam filled used Aircraft, 15" Wheels less tires	21" Laminated, 24" Pneumatic or foam filled used Aircraft, 29" Pneumatic or foam filled used Aircraft, 15" Wheels less tires
	Spring suspension	Standard	Standard	Standard
	Wing leveling adjustment	Easy adjust turnbuckle	Easy adjust turnbuckle	Easy adjust turnbuckle
Shielding		Rubber belting or chain	Rubber belting or chain	Rubber belting or chain
Gearbox warranty		6 years/7 years	8 years	8 years
Deck rust through warranty		10 years	10 years	10 years



**Woods Equipment Company** 2606 South Illinois Route 2, PO Box 1000, Oregon, Illinois 61061 tel 800-319-6637 [www.woodsequipment.com](http://www.woodsequipment.com)

WARNING! Some images may show safety shields removed to provide a better view. Equipment should never be operated without required safety equipment. Always operate machines in accordance with supplied operator's manuals. Some machines in this brochure may be shown with optional equipment. Specifications subject to change without notice. Woods, the Woods logo, Batwing, "The Attachment Experts.", and WoodsCare are trademarks of Woods Equipment Company. All other trademarks, trade names, or service marks not owned by Woods Equipment Company that appear in this brochure are the property of their respective companies or mark holders. © 2009 Woods Equipment Company. All rights reserved. B04092 Revised 05/11